

Overview

Dimensions	442.4 x 43.7 x 496 mm (17.4 x 1.7 x 19.5")
Port Layout	
2.5 GbE RJ45	16 (All PoE+++) (2.5G/1G/100M/10M)
10 GbE RJ45	32 (All PoE+++) (10G/5G/2.5G/1G/100M/10M)
25G SFP28	4 (25G/10G/1G)
Max. PoE Output	Up to PoE+++
Total PoE Availability	200-240V AC Shared Mode: 2,150W 100-120V AC Shared Mode: 1,750W 200-240V AC Redundant Mode: 950W 100-120V AC Redundant Mode: 750W
Redundancy	(2) Hot-Swappable PSUs (4) Hot-Swappable Fans
Layer 3	✓
Form Factor	Rack mount (1U, Full-Depth)
Etherlighting™	✓

Performance

Switching Capacity	920 Gbps
Total Non-Blocking Throughput	460 Gbps
Forwarding Rate	684 Mpps
Supported VLANs	1,000
MAC Address Table Size	128,000
L3 Table Size	
ARP Entries	128,000
IPv4 Routes	256,000

Packet Buffer Size	8 MB
--------------------	------

Access Lists

IPv4	256
------	-----

MAC	256
-----	-----

Layer 3 Features

DHCP Server (Local Networks)	✓
------------------------------	---

DHCP Relay	✓
------------	---

Inter-VLAN Routing (Local Networks)	✓
-------------------------------------	---

Static Routing (Local Networks)	✓
---------------------------------	---

Layer 2 Features

LACP Port Aggregation	✓
-----------------------	---

STP & RSTP	✓
------------	---

QoS (DSCP)	✓
------------	---

Pro AV Profiles (Play, Dante, Q-SYS, NDI, SDVoE, Shure, AES67, Crestron)	✓
--	---

Advanced IGMP Configuration (Querier, Fast Leave, Router Port)	✓
--	---

IGMP Snooping	✓
---------------	---

802.1X Control	✓
----------------	---

MAC-Based ACLs & Device Isolation	✓
-----------------------------------	---

DHCP Snooping & Guarding	✓
--------------------------	---

Egress Rate Limit	✓
-------------------	---

Flow Control	✓
--------------	---

Storm Control	✓
---------------	---

Multicast & Broadcast Rate Limiting	✓
-------------------------------------	---

MAC Address Blocking	✓
----------------------	---

IP-Based ACLs & Network Isolation	✓
MAC-Based Port Restriction	✓
Port Isolation	✓
Port Mirroring	✓
Jumbo Frames	✓
LLDP-MED	✓
Voice VLAN	✓
Loop Protection	✓

Hardware

PoE Ports

PoE+++	48
--------	----

Max. PoE Wattage per Port by PSE

PoE	15.4W
PoE+	30W
PoE++	60W
PoE+++	90W

Max. Power Consumption	250W (Excluding PoE Output) 2400W (Including PoE Output)
------------------------	---

Power Method	(2) Universal input, 100—240V AC, 50/60 Hz
--------------	--

Power Input Method	(2) AC input, Hot-swappable power modules
--------------------	---

Power Supply	(2) Hot-swappable AC/DC 1,200W power modules
--------------	--

Supported Voltage Range	100—240V AC
-------------------------	-------------

Management	Ethernet AR
------------	----------------

Weight	Without mounting brackets: 9.46 kg (20.9 lb) With mounting brackets: 9.56 kg (21.1 lb)
--------	---

Enclosure Material	SGCC steel
--------------------	------------

Mount Material	SGCC steel
Supported Rack Depth	482.6 mm (19") four-post racks Posts depths ranging from 650 to 1,000 mm (25.6–39.4")
LCM Display	1.3" touchscreen
Fan Method	(4) hot-swappable fan modules
ESD Protection	Air: $\pm 30\text{kV}$, contact: $\pm 19\text{kV}$
Ambient Operating Temperature	-5 to 40° C (23 to 104° F)
Ambient Operating Humidity	10 to 90% noncondensing
Etherlighting™	
Ethernet	✓
SFP28	✓
LEDs	
Ethernet	✓
System	✓
NDAA Compliant	✓
Certifications	CE, FCC, IC

Software

Application Requirements	
UniFi Network	Version 9.0.114 and later