

## Overview

Dimensions	Device: 200 x 38 x 20.2 mm (7.9 x 1.5 x 0.8") Table stand: 48.1 x 48 x 55.2 mm (1.9 x 1.9 x 2.2")
Networking Interface	(1) GbE RJ45 port 5G RedCap and LTE
SIM	(1) Nano SIM (4FF) (1) eSIM
PoE Interface	(1) PoE input
Mounting	Desktop stand, wall, window mount (Included)

## Mechanical

Weight	Device: 122 g (4.3 oz) Stand: 138 g (4.9 oz) Wall mount: 66 g ( 2.3 oz)
Enclosure Material	Polycarbonate, aluminum alloy
Mount Material	Galvanized steel, silicone rubber

## Hardware

Management	Ethernet
5G NR	
Category	5G RedCap
Frequency Bands	n1, n3, n5, n7, n8, n20, n26, n28, n40, n41, n77, n78
Max. TX Power	23 dBm
4G LTE	

Frequency Bands	B1, B3, B5, B7, B8, B18, B19, B20, B26, B28, B38, B40, B41, B42, B43
Max. TX Power	HPUE power class 2: 26 dBm
Peak Data Speed	
5G SA	Downlink 220 Mbps / Uplink 120 Mbps
4G LTE	Downlink 195 Mbps / Uplink 100 Mbps
LTE Throughput Speed	Downlink 195 Mbps / Uplink 100 Mbps
Antennas	
Type	(2) Embedded omni-directional cellular antennas
Power Method	PoE
Display	1.14" status display
Buttons	(1) Factory reset
Ambient Operating Temperature	0 to 40 °C (32 to 104 °F)
Ambient Operating Humidity	5 to 95% noncondensing
Certifications	CE
<b>Software</b>	
Application Requirements	
UniFi Network	Version 10.4.57 and later
Mobile App	UniFi iOS™ version 10.35.0 and later UniFi Android™ version 10.38.2 and later